



SPLIT BOLT IN USE

COPPER ALLOY SPLIT BOLT CONNECTOR

RANGE FOR EQUAL RUN AND TAP: 8 SOL - 4 SOL (Ø0.128-Ø0.204)
MINIMUM TAP 16 SOL ; MAX CONDUCTOR 3 #12 STR.
TORQUE (165 IN/LB)

EST. WEIGHT 0.06 LBS

APPROVED

AS DRAWN: _____
 AS NOTED: _____
 DATE: _____

THIS DOCUMENT AND THE CONTENTS THEREOF IS THE PROPERTY OF HARGER INC., AND IS FURNISHED TO YOU FOR INFORMATION ONLY. THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND OF A PROPRIETARY NATURE AND MUST NOT BE DISCLOSED TO THIRD PARTIES WITHOUT THE EXPRESS WRITTEN APPROVAL OF HARGER INC.

LET	REVISION	DATE	BY
-	-	-	-
TOLERANCES UNLESS NOTED:		3RD ANGLE PROJECTION	
FRACTIONAL	+/- 1/64		
.00	+/- .010		
.000	+/- .005		

PART NO. GESB6
 COPPER ALLOY SPLIT BOLT CONNECTOR

DRAWN BY:
 DVBV
 CHECKED BY:
 -
 DATE:
 032608



301 ZIEGLER DRIVE
 GRAYSLAKE, IL 60030
 (847) 548-8700

REVISION:
 -
 SCALE:
 FULL
 SHEET:
 1 OF 1